

## DEAD-TANK GAS CIRCUIT BREAKER STANDARD RATING TABLE\*

	123kV						
Rating	401	kA	50	kA	63	kA	80kA
Voltage (Max kV)	123	123	123	123	123	123	123
BIL (kV Crest)	550	550	550	550	550	550	550
Close/Latch Capability (kA)	104	104	130	130	164	164	208
60Hz withstand (kV)	260	260	260	260	260	260	260
Continuous current (A)	3000	3000	3150	3150	3150	3150	3150
Interrupting current (kA)	40	40	50	50	63	63	80
Interrupting time (cycles)	3	3	3	3	3	3	2

145kV						
40	κA	50	kA	63	kA	80kA
145	145	145	145	145	145	145
650	650	650	650	650	650	650
104	104	130	130	164	164	208
310	310	310	310	310	310	310
3150	3150	3150	3150	3000	3000	3000
40	40	50	50	63	63	80
3	3	3	3	3	3	2
	145 650 104 310 3150 40	650     650       104     104       310     310       3150     3150       40     40	145     145     145       650     650     650       104     104     130       310     310     310       3150     3150     3150       40     40     50	145     145     145     145       650     650     650     650       104     104     130     130       310     310     310     310       3150     3150     3150     3150       40     40     50     50	145     145     145     145     145       650     650     650     650     650       104     104     130     130     164       310     310     310     310     310       3150     3150     3150     3000       40     40     50     50     63	145     145     145     145     145     145       650     650     650     650     650     650       104     104     130     130     164     164       310     310     310     310     310     310       3150     3150     3150     3000     3000       40     40     50     50     63     63

	170kV						
Rating	401	κA	50	kA	63	kA	80kA
Voltage (Max kV)	170	170	170	170	170	170	170
BIL (kV Crest)	750	750	750	750	750	750	750
Close/Latch Capability (kA)	104	104	130	130	164	164	208
60Hz withstand (kV)	365	365	365	365	365	365	365
Continuous current (A)	3000	3000	3000	3000	3000	3000	3000
Interrupting current (kA)	40	40	50	50	63	63	63
Interrupting time (cycles)	3	3	3	3	3	3	2

## Notes:

- Synchronous switching option available for all IPO breakers up to 550kV
- Mixed gas (SF6/CF4) option available for select Gang Operated breakers up to 245kV-50kA
- Mixed gas (SF6/CF4) option available for select IPO breakers up to 362kV-50kA

Independent Pole Operated (IPO)

Gang Operated

IPO breakers are available with synchronous control option for capacitor bank switching, reactor bank switching and transformer switching applications.

<sup>\*</sup>Select max voltages, BIL ratings, continuous currents, and interrupting times may not reflect the maximum values that are available.

If your needs differ, please consult with your local MEPPI sales representative for additional details.

	245kV						
Rating	401	κA	50kA		63kA		80kA
Voltage (Max kV)	245	245	245	245	245	245	245
BIL (kV Crest)	900	900	900	900	900	900	900
Close/Latch Capability (kA)	104	104	130	130	164	164	208
60Hz withstand (kV)	425	425	425	425	425	425	425
Continuous current (A)	3000	3000	3000	3000	3000	3000	3000
Interrupting current (kA)	40	40	50	50	63	63	80
Interrupting time (cycles)	3	3	2 or 3	3	2 or 3	3	2

362kV							
Rating	40	kA	50	)kA	63	kA	80kA
Voltage (Max kV)	362	362	362	362	362	362	362
BIL (kV Crest)	1300	1300	1300	1300	1300	1300	1300
Close/Latch Capability (kA)	104	104	130	130	164	164	208
60Hz withstand (kV)	555	555	555	555	555	555	555
Continuous current (A)	3000	3000	3000	3000	3000	3000	3000
Interrupting current (kA)	40	40	50	50	63	63	80
Interrupting time (cycles)	2	2	2	2	2	2	2

550kV						
Rating	40kA	50kA	63kA			
Voltage (Max kV)	550	550	550			
BIL (kV Crest)	1800	1800	1800			
Close/Latch Capability (kA)	104	130	164			
60Hz withstand (kV)	860	860	860			
Continuous current (A)	3000	3000	3000			
Interrupting current (kA)	40	50	63			
Interrupting time (cycles)	2	2	2			

FFOLV

800kV		
40kA	50kA	63kA
800	800	800
2100	2100	2100
104	130	164
960	960	960
3000	3000	3000
50	50	63
2	2	2

## Notes:

- Synchronous switching option available for all IPO breakers up to 550kV
- Mixed gas (SF6/CF4) option available for select Gang Operated breakers up to 245kV-50kA
- Mixed gas (SF6/CF4) option available for select IPO breakers up to 362kV-50kA

Independent Pole Operated (IPO)

Gang Operated

IPO breakers are available with synchronous control option for capacitor bank switching, reactor bank switching and transformer switching applications.

\*Select max voltages, BIL ratings, continuous currents, and interrupting times may not reflect the maximum values that are available.

If your needs differ, please consult with your local MEPPI sales representative for additional details.

## MITSUBISHI ELECTRIC POWER PRODUCTS, INC.

Corporate Headquarters Thorn Hill Industrial Park 530 Keystone Drive Warrendale, PA 15086 www.meppi.com | 724.772.2555 © 2021 Mitsubishi Electric Power Products, Inc. All Rights Reserved. Printed in USA Publication No. SA0020000002 | March 2021

