

# Spills happen.



**Eliminate the number one cause of indoor ribbon board display failures with Spill Guard™ technology.**

Pixel Pitch	10mm	16mm
Pixel Density (SQM)	10,000	3,906
Pixel Density (SQFT)	929	363
Brightness cd/m <sup>2</sup> (nit)	3,000	3,000
LED Unit Size (Width)	320mm	256mm
Horizontal Viewing Angle*	+70° ~ -70° (140°)	
Vertical Viewing Angle*	+70° ~ -70° (140°)	
Color Processing	14 Bit / 16,384 levels [16 Bit/65,536 levels HDR Option]	
Refresh Rate	2,000 Hz	
Power (Max)**	500W/m <sup>2</sup> (46W/ft <sup>2</sup> )	
Power (Avg)**	167W/m <sup>2</sup> (16W/ft <sup>2</sup> )	
Weight	50kg/m <sup>2</sup> (10.2lb/ft <sup>2</sup> )	

\* Viewing angles based on viewable area.

\*\* Power based on 100~240VAC, 3Ø, 3 Wire + Ground

Excited fans, beverage spills, and ribbon board displays did not mix well — until now. Spill-proof indoor LED panels save time and money on maintenance and repairs. Spill Guard™ technology — the latest LED display innovation from Mitsubishi Electric.

**To learn more, visit  
[Diamond-Vision.com](http://Diamond-Vision.com)  
or call 724-772-2555**

Linked  YouTube



**MITSUBISHI ELECTRIC  
POWER PRODUCTS, INC.**

530 Keystone Drive  
Warrendale, PA 15086  
Phone: 724.772.2555  
[www.diamond-vision.com](http://www.diamond-vision.com)



**DIAMOND  
VISION**  
SYSTEMS DIVISION

Copyright ©2021 Mitsubishi Electric Power Products, Inc. All Rights Reserved.